



Get in touch

01942 206 004
www.invisiblecreations.co.uk
www.procare-ltd.co.uk
hello@invisiblecreations.co.uk



Dual Purpose Grab Rail

Toilet Roll Holder



Assembly Instructions

- 1. Rest both brackets on a flat surface and ensure you have all of the pieces shown above.
- 2. Take the 32mm rail and place it between the brackets.
- 3. Insert one thread-locking bolt through the upper hole on the bracket and into the threaded hole on the rail.
- 4. Using the hex tool provided, tighten the bolt until it is flush with the bracket.
- 5. Repeat steps 3 & 4 on the opposite side.
- 6. Mark out fixing locations on the wall, drill holes if required, and install the item using appropriate fixings.
- 7. Ensure the product is safe for use after fixing to the wall.
- 8. Depress the telescopic toilet roll holder and place it in the lower hole of the bracket.

General Safety Information

- Please ensure these instructions are fully read and implemented. Failure to do so may result in injury to the user. Retain these instructions in a safe place for future reference.
- This product must be correctly assembled, installed, and maintained.
- Non-rusting fixings should be used.
- The product must be installed by a competent professional onto a surface that is deemed suitable and structurally sound.
- Support rails can be slippery when wet, please use with caution.
- The product has been tested to a load of 160KG for 60-seconds in accordance with BS ISO 17966:2016
- Should you see any damage during unpacking or suspect a fault, do not install the product and contact your supplier immediately.